

Vanalar - Valves					Sıcaklığa (°C) göre max. Çalışma basıncı (bar)										
PN	Demir Döküm	Sfero Döküm	Çelik Döküm	Çelik	20	200	250	300	350	400	425	450	500	520	550
	Cast Iron	Ductile Iron	Cast Steel	Steel	120'										
6	GG-25	GGG 38	-----	St-37/2	6 6	5	4.5	3.6							
10	GG-25	GGG 38	GS-45	St-37/2	10 10	8	7	6							
16	GG-25	GGG 38	GS-45	St-37/2	16 16	13	11	10							
			GS-C 25	C 22 N	16 16	14	13	11	10	8					
25	-----	GGG 38	GS-45.5	C 22 N	25 25	-----	18	16							
			GS-C 25		25 25	20	17	16	13						
			GS-22 Mo 4	15 Mo 3		25	22	20	19	18	17				
			GS-17 CrMo 55	13 Cr Mo 44		25	24	23	22	21	18	12			
40	-----	-----	GS-45.5	C 22 N	40 40	32	28	24							
			GS-C 25		40 40	35	32	28	24	21					
			GS-22 Mo 4	15 Mo 3		40	35	31	30	29	28				
			GS-17 CrMo 55	13 Cr Mo 44		40	38	36	35	33	29	19			
63	-----	-----	GS-C 25	C 22 N	63 63 63	36	29	24							
					63 63	50	45	40							
			GS-22 Mo 4	15 Mo 3		63	50	45	40	36	32				
			GS-17 CrMo 55	13 Cr Mo 44		63	50	45	40	36	32	46	45		
100	-----	-----	GS-C 25	C 22 N	100 100 100	80	70	60							
					100 100	80	70	60	56	50					
			GS-22 Mo 4	15 Mo 3		100	87	78	74	72	70				
			GS-17 CrMo 55	13 Cr Mo 44		100	87	78	74	72	70	53	32		
160	-----	-----	GS-C 25	C 22 N	160 160 160	130	112	96							
					160 160	130	112	96	90	80					
			GS-22 Mo 4	15 Mo 3		160	139	125	118	115	112				
			GS-17 CrMo 55	13 Cr Mo 44 10 Cr Mo 9 10		160	139	125	118	115	112	118	79		52
250	-----	-----	GS-C 25	C 22 N	250 250 250	200	175	150							
					250 250	200	175	150	140	125					
			GS-22 Mo 4	15 Mo 3		250	217	195	185	179	174				
			GS-17 CrMo 55	13 Cr Mo 44 10 Cr Mo 9 10		250	217	195	185	179	174	184	124	54	81